

SH101 HOUSE HOLD FIRE BLANKET



SGS | **EN1869:2019**

FEATURES

- ▶ High-temperature resistant fiberglass fabric
- ▶ Suitable for kitchen and household applications
- ▶ Quick-release wall-mounted packaging for rapid deployment
- ▶ Effective on grease fires and small electrical fires
- ▶ Flexible, tear-resistant, and long-lasting design

TECHNICAL SPECIFICATION

Material	Woven Fiberglass Fabric
Maximum Continuous Temperature	550–700 °C
Short-Term Peak Temperature	900–1100 °C
Fabric Thickness	0.43 mm
Fabric Density	430 g/m ²
Standard Size (Kitchen)	1.0 × 1.0 m
Standard Size (General)	1.2 × 1.2 m
Industrial Size	1.5 × 1.5 m / 1.8 × 1.8 m
Test Standards	EN 1869:2019

ORDER DETAILS

- ▶ SH1010 - 1x1x0.43mm Fire Blanket Fiberglass without silicone coating
- ▶ SH1212 - 1.2x1.2x0.43mm Fire Blanket Fiberglass without silicone coating
- ▶ SH1515 - 1.5x1.5x0.43mm Fire Blanket Fiberglass without silicone coating
- ▶ SH1818 - 1.8x1.8x0.43mm Fire Blanket Fiberglass without silicone coating